



EG3800DC/EG3800DDC

- Rated power of 2800 watt, 110/220/230/240V
- Eagle commercial-grade OHV engine
- 12V direct current output
- Automatic voltage regulation by AVR
- Low oil level automatic protection
- Current over current protection
- Capacious fuel tank of 18 liter, for which to run 13 hours constantly
- Frame-type safety generator support
- Wheel components are optional
- Self-starting or remote-starting is optional



Engine model	G240F/G240FD
Engine type	Single cylinder,4stroke, forced cooling ,OHV
Power output	5.2Kw/3600rpm
Bore×Stroke	73mm×58mm (2.9"×2.3")
Displacement	242cc
Compression ratio	8.2:1
Oil capacity	1.1L (0.29gal)
Fuel tank capacity	25L (6.6gal)
Fuel consumption	≤374g/Kw.h
Continuing time	13h
Rated frequency	50 Hz/60 Hz
Rated voltage	110V/115V/120V/220V/ 230V/240
Voltage regulator system	Automatic Voltage Regulation
Rated output	2.8Kw
Max output	3.1Kw
Power factor	1.0
Charging voltage	12V(DC)
Charging current	8.3A(DC)
Starting system	Recoil start/Electric-start
Ignition system	Transistorized magneto ignition
Noise (≤7m)	≤76dB(A)
Dimension	680×540×545 (26.8"×21.3"×21.5")
Net weight	68Kg (150lb)



Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae