



For Construction &
Civil Engineering

PONSTAR
PX Series





Change delivery flange direction and delivery hose will never be bent again.

PX-55022

Great Durability

Suitable for

- Drainage of underground water
- Disposal of residual water from roof tank of buildings, swimming pools, etc.
- Construction site
- Pond / Aquarium usage
- Irrigation
- Home / Domestic application

Specifications

Model		PX-55011	PX-55022
P	Connection Dia	50 mm (2")	
U	Total Head	10 m (32 ft)	
M	Delivery Volume	260 L/min (68 USG/min)	
P			
M	Voltage	AC 110 V	AC 220 V
O	Frequency	50 Hz	

T O R	Out put	400 W	
	Rated Current	3.2 A	
	Consumption	580 W	620 W
	Revolution	3400 rpm	
	Type	Condenser Induction Motor	
	Power Cord	5m	
Standard Accessories		1 Hose Band, 1 Rope (5 m)	
Gross Weight		25kg	
Dimensions LxWxH (mm)		258x500x424	
Packing Unit		2	

Condenser motor requires 3 times starting rated current.

Robin Machineries & Equipment

Tel: 000971-4-2217124

Fax: 000971-4-2234493

POBox: 5229 Dubai, UAE

Email: alawitra@emirates.net.ae

www.alawigroup.ae

